

Chain Sling Powertex 4-leg with Masterlink MC4 and Latch Hooks, Grade 10

Product information



The Chain Sling Powertex 4-leg MC-4 with latch hooks is a four-leg lifting assembly for general industrial use. It features an MC-4 master link with an integrated shortening function, reducing the number of components and creating a more compact, manageable lifting setup.

It is designed for controlled lifting where fast connection, quick length adjustment, and predictable performance are required.

The assembly includes the MC-4 master link, Grade 10 chain, latch hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

Best used for:

- Lifting loads requiring multiple lifting points for stability
- Applications where a compact setup with integrated shortening is preferred
- Repetitive lifting where fast and efficient hook connection improves handling speed

Product benefits

- MC-4 master link integrates shortening functions on all legs, reducing the number of components and simplifying assembly configuration
- Integrated shortening allows quick length adjustment without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter

[... Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Red powder paint

Standard: EN 818-4, AS 3776

(+25 % WLL)

Safety factor: 4:1

Grade: 10

Chain Sling Powertex 4-leg with Masterlink MC4 and Latch Hooks, Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t
241300600100290	6	3	1	3	2.12
241300600200290	6	3	2	3	2.12
241300600300290	6	3	3	3	2.12
241300600400290	6	3	4	3	2.12
241300600500290	6	3	5	3	2.12
241300600600290	6	3	6	3	2.12
241300600700290	6	3	7	3	2.12
241300600800290	6	3	8	3	2.12
241300800100290	8	5.3	1	5.3	3.75
241300800200290	8	5.3	2	5.3	3.75
241300800300290	8	5.3	3	5.3	3.75
241300800400290	8	5.3	4	5.3	3.75
241300800500290	8	5.3	5	5.3	3.75
241300800600290	8	5.3	6	5.3	3.75
241300800700290	8	5.3	7	5.3	3.75
241300800800290	8	5.3	8	5.3	3.75
241301000100290	10	8.4	1	8.4	6
241301000200290	10	8.4	2	8.4	6
241301000300290	10	8.4	3	8.4	6
241301000400290	10	8.4	4	8.4	6
241301000500290	10	8.4	5	8.4	6
241301000600290	10	8.4	6	8.4	6
241301000700290	10	8.4	7	8.4	6
241301000800290	10	8.4	8	8.4	6
241301300200290	13	14	2	14	10
241301300300290	13	14	3	14	10
241301300400290	13	14	4	14	10
241301300500290	13	14	5	14	10
241301300600290	13	14	6	14	10
241301300700290	13	14	7	14	10

Chain Sling Powertex 4-leg with Masterlink MC4 and Latch Hooks, Grade 10

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t
241301300800290	13	14	8	14	10
241301600200290	16	21.2	2	21.2	15
241301600300290	16	21.2	3	21.2	15
241301600400290	16	21.2	4	21.2	15
241301600500290	16	21.2	5	21.2	15
241301600600290	16	21.2	6	21.2	15
241301600700290	16	21.2	7	21.2	15
241301600800290	16	21.2	8	21.2	15