

General use



Overhead cranes



Winch rope



Agriculture and









Steel Wire Rope Ropetex S65 Stainless Steel

Product information









Ropetex S65 is a stainless steel rope, the most commonly used range is from 8 to 38 mm. It can be used for cranes, hoists, slings and a wide range of various other applications.

Ropetex S65 is equipped with an Independent Wire Rope Core (IWRC) which gives it a high breaking strength and dimensionally stability, especially when used on sheaves or drums.

In stainless steel (AISI 316) it's well suited for marine and aggressive environments.

Rope construction: 6x36WS+IWRC Material: AISI 316 / EN 1.4401 Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: EN 12385-4 except material

Fill factor: 0,59

Part code	Rope diameter mm	Tensile strength N/mm²	Finish	Rope lay	Min. breaking force kN	Steel area mm²	Lubrication	Weight kg/100m
108101004620048	10	1,570	Stainless	sZ	56	46	No-Lube	40.9
108101404620048	14	1,570	Stainless	sZ	110	90.2	No-Lube	80.2
108101604620048	16	1,570	Stainless	sZ	143	118	No-Lube	105
108102004620048	20	1,570	Stainless	sZ	224	184	No-Lube	164
108102204620048	22	1,570	Stainless	sZ	270	249.7	No-Lube	198