


Steel Wire Rope Ropetex S42 PVC

Product information



General use



ROPETEX



ROPETEX S42 is a galvanized rope equipped with a Fibre Core (FC) and has a PVC coating. It can be used for various applications such as locking rope, signaling devices, etc but not for lifting. It's most used in small diameters up to 8 mm.

Available with transparent, matt black or a matt Red (RAL 3020) PVC coating.

The PVC coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

[... Read more](#)

Rope construction: 6x7 FC

Marking: According to standard

Temperature range: -30°C up to +70°C

Standard: AS 3569

Standard: EN 12385-4

except from coating

Warning: Not to be used for lifting purposes

Fill factor: 0,47

Steel Wire Rope Ropetex S42 PVC

Technical data

| Part code | Rope diameter mm | Inner diameter mm | Colour | Tensile strength N/mm ² | Min. breaking force kN | Steel area mm ² | Lubrication | Weight kg/100m |
|-----------------|---------------------|----------------------|-------------|---------------------------------------|---------------------------|-------------------------------|-------------|-------------------|
| 105130030020010 | 3 | 2 | transparent | 1,770 | 2.35 | 3.32 | Dry | 2.1 |
| 105130040020010 | 4 | 2 | transparent | 1,770 | 2.35 | 5.9 | Dry | 2.7 |
| 105130040030010 | 4 | 3 | transparent | 1,770 | 5.29 | 5.9 | Dry | 4.1 |
| 105130040030014 | 4 | 3 | Black | 1,770 | 5.29 | 5.9 | Dry | 4.1 |
| 105130040030012 | 4 | 3 | Red | 1,770 | 5.29 | 5.9 | Dry | 4.1 |
| 105130050030010 | 5 | 3 | transparent | 1,770 | 5.29 | 9.23 | Dry | 5.3 |
| 105130050030012 | 5 | 3 | Red | 1,770 | 5.29 | 9.23 | Dry | 5.3 |
| 105130060040010 | 6 | 4 | transparent | 1,770 | 9.4 | 13.3 | Dry | 8.3 |
| 105130070050010 | 7 | 5 | transparent | 1,770 | 14.7 | 18.1 | Dry | 12.1 |
| 105130080060010 | 8 | 6 | transparent | 1,770 | 21.2 | 23.6 | Dry | 15.2 |