
Steel Wire Rope Ropetex S33 PVC

Product information



General use



Slings



ROPETEX

sZ G

ROPETEX S33 is a galvanized rope equipped with a Wire Strand Core (WSC) and has a black PVC coating. It can be a good choice for basic lifting applications such as lifting slings, security rope in studios/theaters premises, etc. It´s most used in small diameters up to 8 mm. Ropetex S33 is equipped with a steel core, which gives the rope less flexible than S14 PVC but has higher strength.

The PVC coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

... *Read more*

Rope construction: 6x19M-WSC
Marking: According to standard
Temperature range: -30°C up to +70°C
Standard: EN 12385-4
except from coating
Note: End terminations must be placed on exposed steel wire rope. PVC-coating must be removed before applying a ferrule, and ferrule size is to be determined by the steel wire ropes dimensions. Periodic inspections of the steel wire rope can be made difficult due to the PVC-coating. The end user must handle this risk in a proper way, by for instance replacing the wire rope in time.

Fill factor: 0,53

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Steel Wire Rope Ropetex S33 PVC

Technical data

Part code	Rope diameter mm	Inner diameter mm	Colour	Tensile strength N/mm²	Min. breaking force kN	Steel area mm²	Weight kg/100m
105130040030034	4	3	Black	1,770	5.77	3.76	4.2
105130080060034	8	6	Black	1,770	23.1	15	16.1

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved