Lifting Solutions Group
Axel Johnson International

ROPETEX Traction Lube 40

Product information



ROPETEX

Ropetex Traction Lube 40 is a synthetic lubricant which coats wire surfaces with a slip-resistant film. It is designed for situations in which frictional grip is vital, because it provides internal lubrication whilst avoiding excessive build-up with repeated applications.

Typical applications: Lifts, elevators and traction hoists.

Application methods: Portable sprayer or brushing/dripping.
Minimum application temperature: -5°C (product should be kept to at least 10°C for 48 hours before application).
Color/texture: White water fluid.
NLGI Grade: Solvent liquid
4-ball weld load: > 110 kgf

Available in a 20 liter drum.

Extra:
Do not forget to download the white paper with a lot of useful information about wire rope lubricants. It is free! (see the 'documents' tab).

... *Read more*

Temperature range: -55°C up to +40°C

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

ROPETEX Traction Lube 40

Technical data

Part code	Description
142502000020	Ropetex Traction Lube 40, 20 lit drum

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved