Lifting Solutions Group
Axel Johnson International

Fixed Spreader Beams PALF

Product information



The PALF fixed spreader beam is designed for lifting loads while maintaining controlled spacing between lifting points. It is suited to industrial handling operations using synthetic slings, wire ropes or similar lifting accessories, with articulated rotating hooks supporting flexible load connection and alignment. Equipped with 2 articulated rotaring hooks with forged safety latches.

Best used for:

- Repetitive lifting operations with a fixed lifting geometry.
- Handling loads with synthetic slings, chain slings or wire rope assemblies.

Product benefits:

- Fixed beam design supports repeatable lifting setups.
- Articulated rotating hooks improve load connection flexibility.
- Forged safety latches support secure hook engagement.
- Tear-resistant eyelets suit slings, cables and wire ropes.
- No structural welds and FEM 5 classification support demanding industrial use.
- Delivered with user's and maintenance manual and EC certificate of compliance

... Read more

Material: Steel
Marking: According to standard, CE-mark
Finish: RAL 1028 yellow
Standard: EN 13155


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Fixed Spreader Beams PALF

Blueprint



Technical data

Part code	WLL ton	Length m	L mm	LT mm	HP mm	a mm	b mm	Weight kg
6205PALF1T1AC	1	1	1,000	1,100	332	60	80	25
6205PALF1T2AC	1	2	2,000	2,100	332	60	80	42
6205PALF1T3AC	1	3	3,000	3,100	350	60	80	72
6205PALF1T4AC	1	4	4,000	4,100	369	60	80	116
6205PALF1T5AC	1	5	5,000	5,100	387	60	80	170
6205PALF1T6AC	1	6	6,000	6,100	387	60	80	202
6205PALF1T7AC	1	7	-	-	-	-	-	280
6205PALF1T8AC	1	8	-	-	-	-	-	318
6205PALF2T1AC	2	1	1,000	1,100	406	80	120	28
6205PALF2T2AC	2	2	2,000	2,100	442	80	120	67
6205PALF2T3AC	2	3	3,000	3,100	460	80	120	111
6205PALF2T4AC	2	4	4,000	4,100	479	80	120	168
6205PALF2T5AC	2	5	5,000	5,100	499	80	120	238
6205PALF2T6AC	2	6	6,000	6,100	499	80	120	281
6205PALF2T7AC	2	7	-	-	-	-	-	371
6205PALF2T8AC	2	8	-	-	-	-	-	486
6205PALF3T1AC	3	1	1,000	1,100	483	100	180	37
6205PALF3T2AC	3	2	2,000	2,100	521	100	180	83
6205PALF3T3AC	3	3	3,000	3,100	539	100	180	134
6205PALF3T4AC	3	4	4,000	4,100	558	100	180	198
6205PALF3T5AC	3	5	5,000	5,100	576	100	180	278
6205PALF3T6AC	3	6	6,000	6,100	596	100	180	378

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Fixed Spreader Beams PALF

Technical data

Part code	WLL ton	Length m	L mm	LT mm	HP mm	a mm	b mm	Weight kg
6205PALF3T7AC	3	7	-	-	-	-	-	495
6205PALF3T8AC	3	8	-	-	-	-	-	561
6205PALF4T1AC	4	1	1,000	1,100	502	100	180	48
6205PALF4T2AC	4	2	2,000	2,100	539	100	180	100
6205PALF4T3AC	4	3	3,000	3,100	558	100	180	158
6205PALF4T4AC	4	4	4,000	4,100	594	100	180	267
6205PALF4T5AC	4	5	5,000	5,100	614	100	180	368
6205PALF4T6AC	4	6	6,000	6,100	614	100	180	432
6205PALF4T7AC	4	7	-	-	-	-	-	573
6205PALF4T8AC	4	8	-	-	-	-	-	782
6205PALF5T1AC	5	1	1,000	1,100	558	100	180	56
6205PALF5T2AC	5	2	2,000	2,100	596	100	180	117
6205PALF5T3AC	5	3	3,000	3,100	616	100	180	183
6205PALF5T4AC	5	4	4,000	4,100	651	100	180	303
6205PALF5T5AC	5	5	5,000	5,100	671	100	180	420
6205PALF5T6AC	5	6	6,000	6,100	671	100	180	492
6205PALF5T7AC	5	7	-	-	-	-	-	693
6205PALF5T8AC	5	8	-	-	-	-	-	785
6205PALF6T1AC	6	1	1,000	1,100	560	100	180	61
6205PALF6T2AC	6	2	2,000	2,100	609	100	180	121
6205PALF6T3AC	6	3	3,000	3,100	647	100	180	215
6205PALF6T4AC	6	4	4,000	4,100	667	100	180	308
6205PALF6T5AC	6	5	5,000	5,100	683	100	180	425
6205PALF6T6AC	6	6	6,000	6,100	720	100	180	602
6205PALF6T7AC	6	7	-	-	-	-	-	699
6205PALF6T8AC	6	8	-	-	-	-	-	1,041
6205PALF8T1AC	8	1	1,000	1,100	624	100	180	76
6205PALF8T2AC	8	2	2,000	2,100	684	100	180	165
6205PALF8T3AC	8	3	3,000	3,100	703	100	180	250
6205PALF8T4AC	8	4	4,000	4,100	758	100	180	433
6205PALF8T5AC	8	5	5,000	5,100	759	100	180	525

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fixed Spreader Beams PALF

Technical data

Part code	WLL ton	Length m	L mm	LT mm	HP mm	a mm	b mm	Weight kg
6205PALF8T6AC	8	6	6,000	6,100	808	100	180	795
6205PALF8T7AC	8	7	-	-	-	-	-	930
6205PALF8T8AC	8	8	-	-	-	-	-	1,234
6205PALF10T1AC	10	1	1,000	1,100	664	100	180	91
6205PALF10T2AC	10	2	2,000	2,100	720	100	180	190
6205PALF10T3AC	10	3	3,000	3,100	739	100	180	288
6205PALF10T4AC	10	4	4,000	4,100	774	100	180	440
6205PALF10T5AC	10	5	5,000	5,100	824	100	180	687
6205PALF10T6AC	10	6	6,000	6,100	824	100	180	804
6205PALF10T7AC	10	7	-	-	-	-	-	1,096
6205PALF10T8AC	10	8	-	-	-	-	-	1,240

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved