Lifting Solutions Group
Axel Johnson International

H-bar Adjustable Spreader Beams PALHR

Product information



The PALHR H-bar adjustable spreader beam is a low-headroom lifting beam for handling loads with adjustable lifting points. It is used when hook positions and secondary beam spacing need to be adapted to the load geometry. Equipped with 4 articulated, rotaring hooks with forged safety latches.

Best used for:

- Industrial lifting where four adjustable hook points are required.
- Applications with limited headroom and varied load dimensions.

Product benefits:

- Adjustable hooks support accurate positioning on secondary beams.
- Adjustable secondary beams help match different load widths.
- Four articulated rotating hooks simplify load connection.
- Forged safety latches support secure hook engagement.
- Delivered with user's and maintenance manual and EC certificate of compliance

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Finish: RAL 1028 yellow
Standard: EN 13155


Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

H-bar Adjustable Spreader Beams PALHR

Blueprint



Technical data

Part code	WLL ton	Length m	Width m	L max. mm	L min. mm	l max mm	l min mm	LT mm	lt mm	HP mm	a mm	b mm	Weight kg
6205PALHR1T11AC	1	1	1	1,000	500	1,000	500	1,200	1,100	333	60	80	89
6205PALHR1T21AC	1	2	1	2,000	1,000	1,000	500	2,200	1,100	333	60	80	111
6205PALHR1T31AC	1	3	1	3,000	1,000	1,000	500	3,200	1,100	333	60	80	111
6205PALHR1T32AC	1	3	2	3,000	1,000	2,000	1,000	3,200	2,100	333	60	80	171
6205PALHR1T41AC	1	4	1	4,000	2,000	1,000	500	4,200	1,100	333	60	80	178
6205PALHR1T42AC	1	4	2	4,000	2,000	2,000	1,000	4,200	2,100	333	60	80	214
6205PALHR2T11AC	2	1	1	1,000	500	1,000	500	1,200	1,100	353	80	120	91
6205PALHR2T21AC	2	2	1	2,000	1,000	1,000	500	2,200	1,100	353	80	120	126
6205PALHR2T31AC	2	3	1	3,000	1,000	1,000	500	3,200	1,100	353	80	120	171
6205PALHR2T32AC	2	3	2	3,000	1,000	2,000	1,000	3,200	2,100	363	80	120	226
6205PALHR2T41AC	2	4	1	4,000	2,000	1,000	500	4,200	1,100	353	80	120	229
6205PALHR2T42AC	2	4	2	4,000	2,000	1,000	500	4,200	1,100	353	80	120	229
6205PALHR3T11AC	3	1	1	1,000	500	1,000	500	1,200	1,100	413	100	180	94
6205PALHR3T21AC	3	2	1	2,000	1,000	1,000	500	2,200	1,100	413	100	180	143
6205PALHR3T31AC	3	3	1	3,000	1,000	1,000	500	3,200	1,100	413	100	180	195
6205PALHR3T41AC	3	4	1	4,000	2,000	1,000	500	4,200	1,100	413	100	180	260
6205PALHR3T32AC	3	3	2	3,000	1,000	2,000	1,000	3,200	2,100	423	100	180	284
6205PALHR3T42AC	3	4	2	4,000	2,000	2,000	1,000	4,200	2,100	457	100	180	350
6205PALHR4T11AC	4	1	1	1,000	500	1,000	500	1,200	1,100	452	100	180	138
6205PALHR4T21AC	4	2	1	2,000	1,000	1,000	500	2,200	1,100	452	100	180	177
6205PALHR4T31AC	4	3	1	3,000	1,000	1,000	500	3,200	1,100	452	100	180	238
6205PALHR4T32AC	4	3	2	3,000	1,000	2,000	1,000	3,200	2,100	447	100	180	343

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

H-bar Adjustable Spreader Beams PALHR

Technical data

Part code	WLL ton	Length m	Width m	L max. mm	L min. mm	l max mm	l min mm	LT mm	lt mm	HP mm	a mm	b mm	Weight kg
6205PALHR4T41AC	4	4	1	4,000	2,000	1,000	500	4,200	1,100	452	100	180	347
6205PALHR4T42AC	4	4	2	4,000	2,000	2,000	1,000	4,200	2,100	447	100	180	452
6205PALHR5T11AC	5	1	1	1,000	500	1,000	500	1,200	1,100	467	100	180	146
6205PALHR5T21AC	5	2	1	2,000	1,000	1,000	500	2,200	1,100	467	100	180	208
6205PALHR5T31AC	5	3	1	3,000	1,000	1,000	500	3,200	1,100	467	100	180	276
6205PALHR5T32AC	5	3	2	3,000	1,000	2,000	1,000	3,200	2,100	447	100	180	366
6205PALHR5T41AC	5	4	1	4,000	2,000	1,000	500	4,200	1,100	467	100	180	397
6205PALHR5T42AC	5	4	2	4,000	2,000	2,000	1,000	4,200	2,100	447	100	180	487
6205PALHR6T11AC	6	1	1	1,000	500	1,000	500	1,200	1,100	467	100	180	177
6205PALHR6T21AC	6	2	1	2,000	1,000	1,000	500	2,200	1,100	467	100	180	260
6205PALHR6T31AC	6	3	1	3,000	1,000	1,000	500	3,200	1,100	467	100	180	320
6205PALHR6T41AC	6	4	1	4,000	2,000	1,000	500	4,200	1,100	467	100	180	412
6205PALHR6T32AC	6	3	2	3,000	1,000	2,000	1,000	3,200	2,100	447	100	180	427
6205PALHR6T42AC	6	4	2	4,000	2,000	2,000	1,000	4,200	2,100	447	100	180	520
6205PALHR8T11AC	8	1	1	1,000	500	1,000	500	1,250	1,100	510	100	180	209
6205PALHR8T21AC	8	2	1	2,000	1,000	1,000	500	2,250	1,100	510	100	180	293
6205PALHR8T31AC	8	3	1	3,000	1,000	1,000	500	3,250	1,100	510	100	180	380
6205PALHR8T32AC	8	3	2	3,000	1,000	2,000	1,000	3,250	2,100	510	100	180	506
6205PALHR8T41AC	8	4	1	4,000	2,000	1,000	500	4,250	1,100	530	100	180	568
6205PALHR8T42AC	8	4	2	4,000	2,000	2,000	1,000	4,250	2,100	530	100	180	692
6205PALHR10T11AC	10	1	1	1,000	500	1,000	500	1,250	1,100	558	100	180	223
6205PALHR10T21AC	10	2	1	2,000	1,000	1,000	500	2,250	1,100	558	100	180	325
6205PALHR10T31AC	10	3	1	3,000	1,000	1,000	500	3,250	1,100	558	100	180	426
6205PALHR10T32AC	10	3	2	3,000	1,000	2,000	1,000	3,250	2,100	558	100	180	567
6205PALHR10T41AC	10	4	1	4,000	2,000	1,000	500	4,250	1,100	578	100	180	582
6205PALHR10T42AC	10	4	2	4,000	2,000	2,000	1,000	4,250	2,100	578	100	180	707

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved