Lifting Solutions Group
Axel Johnson International

Adjustable Spacer Spreader Bars PALBAR

Product information



The PALBAR adjustable spacer spreader bar is designed for lifting operations where lifting point spacing must be adapted to different load dimensions. Its movable hanger system allows hook position adjustment while maintaining a low-headroom lifting configuration suitable for use with synthetic slings, cables, and similar lifting accessories.

Best used for:

- Lifting loads with varying lifting point centres.
- Low-headroom lifting applications requiring adjustable hook spacing.

Product benefits:

- Adjustable hook positions with movable hangers for load flexibility.
- Tear-resistant eyelets suit synthetic slings and wire rope assemblies.
- No structural welds in the main load-bearing structure.
- C2 polyester powder-coated finish for indoor industrial environments.
- Delivered with user's and maintenance manual and EC certificate of compliance

... Read more

Material: Steel
Marking: According to standard, CE-mark
Finish: RAL 1028 yellow
Standard: EN 13155

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Adjustable Spacer Spreader Bars PALBAR

Blueprint



Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Adjustable Spacer Spreader Bars PALBAR

Technical data

Part code	WLL ton	Length m	L min. mm	L max. mm	A mm	B mm	C mm	D mm	E mm	F mm	HP mm	Weight kg
6205PALBAR1T215SM	1	2	1,500	2,000	2,060	210	100	15	2	2	248	21.43
6205PALBAR1T32SM	1	3	2,000	3,000	3,060	210	100	15	2	2	248	28
6205PALBAR1T425SM	1	4	2,500	4,000	4,060	210	100	15	2	2	248	35.08
6205PALBAR1T53SM	1	5	3,000	5,000	5,060	210	100	15	2	2	248	42.26
6205PALBAR2T215SM	2	2	3,000	5,000	5,060	210	100	15	2	2	248	25.01
6205PALBAR2T32SM	2	3	2,500	4,000	4,060	210	100	15	2	2	248	31.1
6205PALBAR2T425SM	2	4	1,500	2,000	2,060	210	100	15	2	2	248	39.22
6205PALBAR2T53SM	2	5	2,000	3,000	3,060	210	100	15	2	2	248	47.43
6205PALBAR3T215SM	3	2	1,500	2,000	2,069	275	150	15	3.25	2	332	43.81
6205PALBAR3T32SM	3	3	2,500	4,000	4,069	275	150	15	3.25	2	332	55.06
6205PALBAR3T425SM	3	4	2,000	3,000	3,069	275	150	15	3.25	2	332	69.56
6205PALBAR3T53SM	3	5	3,000	5,000	5,069	275	150	15	3.25	2	332	82.7
6205PALBAR5T215SM	5	2	1,500	2,000	2,069	275	150	15	4.75	3.25	332	56.13
6205PALBAR5T32SM	5	3	2,500	4,000	4,069	275	150	15	4.75	3.25	332	72.3
6205PALBAR5T425SM	5	4	3,000	5,000	5,069	275	150	15	4.75	3.25	332	103.54
6205PALBAR5T53SM	5	5	2,000	3,000	3,069	275	150	15	4.75	3.25	332	110.86
6205PALBAR8T215SM	8	2	1,500	2,000	2,070	325	200	20	6.5	4.75	400	82.61
6205PALBAR8T32SM	8	3	3,000	5,000	5,070	325	200	20	6.5	4.75	400	104.66
6205PALBAR8T425SM	8	4	2,000	3,000	3,070	325	200	20	6.5	4.75	400	133.56
6205PALBAR8T53SM	8	5	2,500	4,000	4,070	325	200	20	6.5	4.75	400	158.51
6205PALBAR10T215SM	10	2	2,500	4,000	4,070	325	200	20	8.5	6.5	417	82.61
6205PALBAR10T32SM	10	3	2,000	3,000	3,070	325	200	20	8.5	6.5	417	104.66
6205PALBAR10T425SM	10	4	1,500	2,000	2,070	325	200	20	8.5	6.5	417	133.56
6205PALBAR10T53SM	10	5	3,000	5,000	5,070	325	200	20	8.5	6.5	417	158.51

Certex Latvija
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved