

## HPJ S Hydraulic Pulling Cylinder

### Product information



Holmatro pulling cylinders (HPJ) – Spring return

#### Unique specifications:

- Compact
- Suitable for pulling, lifting, tensioning in all positions
- Protected against over pressure; A418 valve

#### Standard supplied with:

- High flow female coupler A118, with pressure relief valve A418

#### Accessories:

- Pulling eyes (art. No 100.181.051) and clevis eyes (art. No 100.181.056): 2 of both per cylinder = mandatory
- Protection spring (art. No. 100.581.160) = optional

#### Also available:

- Accessories
- Hydraulic pump units 700bar to control your system
- Hydraulic hoses 700bar
- System components to complete your hydraulic system

**Material:** Steel

**Note:** Protection Spring, Pulling eyes and clevis eyes to be ordered separately (2 pcs per cylinder)

| Part code     | Code        | WLL ton | stroke length mm | required oil cc | A   | B mm | C mm | D2 mm | F mm | G mm | H tread size | J mm | P mm | Weight kg |
|---------------|-------------|---------|------------------|-----------------|-----|------|------|-------|------|------|--------------|------|------|-----------|
| 5211100131001 | HPJ 11 S 15 | 11      | 150              | 236             | 320 | 92   | 40   | 85    | 250  | 470  | M38x1.5      | 30   | 38   | 11.5      |
| 5211100131011 | HPJ 30 S 15 | 30      | 150              | 623             | 470 | 118  | 40   | 85    | 380  | 620  | M38x1.5      | 40   | 44   | 26        |
| 5211100131021 | HPJ 60 S 15 | 60      | 150              | 1,272           | 530 | 157  | 60   | 85    | 400  | 680  | M54x1.5      | 60   | 52   | 45        |

# Blueprint

