Lifting Solutions Group
Axel Johnson International

# Chain SA/S - EN818-2 Gr. 10

## Product information



**General:** Chain for lifting or lashing (other safety factor). Available in 2 different qualities

**Star Alloy (SA/S)**

- Working temperature: max. 200ºC
- Grade Marking: "10" on link every 300mm (up to 16mm) others every 900 mm.
- Surface: Purple varnished

**Star Alloy Plus+ (SAP/S):** for working temperatures up to 380°C (Available on request)

... *Read more*

**Material:** Alloy steel.
**Marking:** According to standard
**Temperature range:** Star Alloy SA/S: -40°C up to 200°C - Star Alloy Plus+ SAP/S: -40°C up to 380°C
**Standard:** EN 818-2
*higher capacity*
**Warning:** Not to be heat treated.

**Safety factor:** 4:1
**Grade:** 10

**Certex Latvija**
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Chain SA/S - EN818-2 Gr. 10

## Blueprint



## Technical data

| Part code | Chain diameter mm | WLL ton | Min. breaking force kN | Pitch Length mm | D mm | P mm | Li min. mm | Le max. mm | Weight kg/m |
|---|---|---|---|---|---|---|---|---|---|
| 203500600000050 | 6 | 1.4 | 56.5 | 18 | 6 | 18 | 8.7 | 22 | 0.96 |
| 203500800000050 | 8 | 2.5 | 101 | 24 | 8 | 24 | 10.9 | 29 | 1.57 |
| 203501000000050 | 10 | 4 | 157 | 30 | 10 | 30 | 13.5 | 36 | 2.46 |
| 203501300000050 | 13 | 6.7 | 265 | 39 | 13 | 39 | 17.5 | 47 | 4.18 |
| 203501600000050 | 16 | 10 | 402 | 48 | 16 | 48 | 21.5 | 58 | 6.28 |
| 203501900000050 | 19 | 14 | 567 | 57 | 19 | 57 | 26.6 | 69 | 8.9 |
| 203502200000050 | 22 | 19 | 760 | 66 | 22 | 66 | 29.5 | 79 | 11.88 |

**Certex Latvija**
info@certex.lv
+371 67611882

© November 2026 - All Rights Reserved