



Master Link assembly Pewag VMWP

Product information

Enlarged master link assembly for creating II- III- and IV-leg chain slings for all chain dimensions.

Material: Alloy steel.

Marking: According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type.

Temperature range: -60°C up to +300°C.

Finish: Light blue powdercoated.

Standard: EN 1677-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 12

| Part code | Code | WLL ton | dmm mm | d1 mm mm | e mm mm | smm mm | t mm | t1 mm mm | w mm mm | w1mm mm | Weight kg |
|--------------|-----------------|---------|--------|----------|---------|--------|------|----------|---------|---------|-----------|
| 403100430030 | VMWP 2- 7/8 | 4.25 | 19 | 13 | 214 | 14 | 160 | 54 | 95 | 25 | 1.47 |
| 403100880030 | VMWP 2-10/4-7/8 | 8.8 | 27 | 17 | 260 | 20 | 190 | 70 | 110 | 34 | 3.45 |
| 403101230030 | VMWP 2-13/4-10 | 12.3 | 33 | 20 | 315 | 26 | 230 | 85 | 130 | 40 | 6.28 |
| 403102120030 | VMWP 4-13 | 21.2 | 38 | 27 | 415 | 29 | 275 | 140 | 150 | 65 | 11.5 |
| 403102650030 | VMWP 4-16 | 26.5 | 38 | 33 | 425 | 29 | 275 | 150 | 150 | 70 | 13.8 |

Blueprint

