



Celšanas cilpa Starpoint VRS-F ar regulējamu garumu









Preces apraksts

- 360° regulējams
- vairākas reizes augstāka WLL nekā DIN 580 cilpai
- Easy-Fit-Key vieglai montāžai un demontāžai

Drošības koeficients: 4:1

Artikula Nr.	Celtpēja	B (mm)	C (mm)	D (mm)	E (mm)	G (mm)	I (mm)	K (mm)	L (mm)	M (mm)	N (mm)	T (mm)
421100041110	0,4	11	9	25	25	30	16,3	47	16-70	M10	6	35
421100081110	0,75	13	10	30	30	34	19,8	56	18-150	M12	8	42
421100151110	1,5	15	13	35	36	40	23,5	65	35	M16	10	49
421100151115	1,5	15	13	35	36	40	23,5	65	120	M16	10	49
421100151116	1,5	15	13	35	36	40	23,5	65	24-120	M16	10	49
421100231110	2,3	17	16	40	41	50	29,3	76	120	M20	12	58
421100231115	2,3	17	16	40	41	50	29,3	76	160	M20	12	58
421100231116	2,3	17	16	40	41	50	29,3	76	30-160	M20	12	58
421100321110	3,2	20	19	49	51	60	35	92	36-140	M24	14	70
421100451110	4,5	26	24	60	66	75	44	114	45-190	M30	17	87

Tehniskā informācija

Celšanas metode											
Zaru skaits	1	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4	
Celšanas leņķis β	0°-7°	90°	0°-7°	90°	0-45°	>45-60°	Nesim	0-45°	>45-60°	Nesim	
Faktors		1		2	1.4	1	1	2.1	1.5	1	
Drošības faktors 4:1	Maksimālajam kopējam slodzes svaram >G< metriskajās tonnās, pievilkts un noregulēts atbilstoši spēka virzienam										
M6	1/4"-20UNC	0.5	0.1	1	0.2	0.14	0.1	0.1	0.21	0.15	0.1

Drošības faktors 4:1

M8	5/16"-18UNC	1	0.3	2	0.6	0.42	0.3	0.3	0.63	0.45	0.3
M8x1	-										
M10	3/8"-16UNC	1	0.4	2	0.8	0.56	0.4	0.4	0.84	0.6	0.4
M10x1	7/16"-14UNC										
M12	1/2"-13UNC	2	0.75	4	1.5	1	0.75	0.75	1.57	1.12	0.75
M12x1,5	-										
M14	-										
M16	5/8"-11UNC	4	1.5	8	3	2.1	1.5	1.5	3.15	2.25	1.5
M16x1,5	-										
M18	3/4"-16UNF										
M20	3/4"-10UNC	6	2.3	12	4.6	3.22	2.3	2.3	4.83	3.45	2.3
M20x2	-										
M22	7/8"-9UNC										
M24	1"-8UNC	8	3.2	16	6.4	4.5	3.2	3.2	6.7	4.8	3.2
M24x2	1 1/8"-8UN										
M27	1 1/8"-7UNC										
M30	1 1/4"-8UN	12	4.5	24	9	6.3	4.5	4.5	9.5	6.75	4.5
M30x2	1 1/4"-7UNC										
M33	-										
M36	1 1/2"-8UN	16	7	32	14	9.8	7	7	14.7	10.5	7
M36x3	1 1/2"-6UNC										
M42	1 3/4"-5UNC	24	9	48	18	12.6	9	9	18.9	13.5	9
M48	2"-4,5UNC	32	12	64	24	16.8	12	12	25.2	18	12
M56	-	50	16	100	32	22.4	16	16	33.6	24	16
M64	-	60	20	120	40	28	20	20	42	30	20

Drošības faktors 4:1

Maksimālajam kopējam slodzes svaram >G< metriskajās tonnās, pievilkts un noregulēts atbilstoši spēka virzienam

Rasējums

