



Celšanas cilpa Starpoint RUD VRS









Preces apraksts

- 360° regulējams slodzes virzienā
- Lielāks WLL nekā DIN 580
- Pieejams Easy-fit vieglai montāžai un demontāžai, skatiet VRS-F tipu

Drošības koeficients: 4:1

Artikula Nr.	Celtpēja tonnas	B (mm)	C (mm)	D (mm)	E (mm)	G (mm)	I (mm)	K (mm)	L (mm)	M (mm)	N (mm)	T (mm)	Svars kg
421100011272	0,1	9	7	20	23	28	13	37	9	M6	6	28	0,07
421100031270	0,3	11	9	25	25	30	16,3	47	12	M8	6	35	0,11
421100041270	0,4	11	9	25	25	30	16,3	47	15	M10	6	35	0,11
421100081270	0,75	13	10	30	30	34	19,8	56	18	M12	8	42	0,19
421100081275	0,75	13	10	30	30	34	19,8	56	18	M14	8	42	0,2
421100151270	1,5	15	13	35	36	40	23,5	65	24	M16	10	49	0,32
421100231270	2,3	17	16	40	41	50	29,3	76	30	M20	12	58	0,54
421100321270	3,2	20	19	49	51	60	35	92	36	M24	14	70	0,86
421100451270	4,5	26	24	60	66	75	44	114	45	M30	17	87	1,5
421100701270	7	32	29	73	76	98	53	135	54	M36	22	104	3,3

Tehniskā informācija

Celšanas metode										
Zaru skaits	1	1	2	2	2	2	2	3 / 4	3 / 4	3 / 4
Celšanas leņķis β	0°-7°	90°	0°-7°	90°	0-45°	>45-60°	Nesim	0-45°	>45-60°	Nesim
Faktors		1		2	1.4	1	1	2.1	1.5	1
Drošības faktors 4:1	Maksimālajam kopējam slodzes svaram >G< metriskajās tonnās, pievilkts un noregulēts atbilstoši spēka virzienam									

Drošības faktors 4:1

M6	1/4"-20UNC	0.5	0.1	1	0.2	0.14	0.1	0.1	0.21	0.15	0.1
M8	5/16"-18UNC	1	0.3	2	0.6	0.42	0.3	0.3	0.63	0.45	0.3
M8x1	-										
M10	3/8"-16UNC	1	0.4	2	0.8	0.56	0.4	0.4	0.84	0.6	0.4
M10x1	7/16"-14UNC										
M12	1/2"-13UNC	2	0.75	4	1.5	1	0.75	0.75	1.57	1.12	0.75
M12x1,5	-										
M14	-										
M16	5/8"-11UNC	4	1.5	8	3	2.1	1.5	1.5	3.15	2.25	1.5
M16x1,5	-										
M18	3/4"-16UNF										
M20	3/4"-10UNC	6	2.3	12	4.6	3.22	2.3	2.3	4.83	3.45	2.3
M20x2	-										
M22	7/8"-9UNC										
M24	1"-8UNC	8	3.2	16	6.4	4.5	3.2	3.2	6.7	4.8	3.2
M24x2	1 1/8"-8UN										
M27	1 1/8"-7UNC										
M30	1 1/4"-8UN	12	4.5	24	9	6.3	4.5	4.5	9.5	6.75	4.5
M30x2	1 1/4"-7UNC										
M33	-										
M36	1 1/2"-8UN	16	7	32	14	9.8	7	7	14.7	10.5	7
M36x3	1 1/2"-6UNC										
M42	1 3/4"-5UNC	24	9	48	18	12.6	9	9	18.9	13.5	9
M48	2"-4,5UNC	32	12	64	24	16.8	12	12	25.2	18	12
M56	-	50	16	100	32	22.4	16	16	33.6	24	16
M64	-	60	20	120	40	28	20	20	42	30	20

Drošības faktors 4:1

Maksimālajam kopējam slodzes svaram >G< metriskajās tonnās, pievilkts un noregulēts atbilstoši spēka virzienam

Rasējums

